

# SAFETY DATA SHEET

## SECTION 1 – IDENTIFICATION

**PRODUCT NAME:** Twinkle Toes -Glitter  
**SUPPLIER:** Twinkle Products Inc.  
**PHONE NUMBER:** 541-312-2028

## SECTION 2 – HAZARDS IDENTIFICATION

**FLAMMABILITY:** Highly Flammable  
**EYE CONTACT:** May cause irritation both liquid and vapor  
**SKIN CONTACT:** Mild skin Irritant, can cause non-allergic contact dermatitis.  
**INHALATION:** Prolonged inhalation may be harmful.  
Can cause drowsiness, headaches, nausea, vomiting and narcosis  
May cause lung irritation.  
**INGESTION:** Causes gastro-intestinal irritation, nausea, vomiting and diarrhea  
**OTHER CHRONIC EFFECTS:** NONE KNOWN

## SECTION 3 – HAZARDOUS INGREDIENTS

Hazardous Ingredients	CAS #	%	Hazard Symbol	Risk Phrases
Ethyl Acetate	141-78-6	20-35%	F, XI	R11, R36, R66, R67
Butyl Acetate	123-86-4	20-35%	F	R10, R66, R67
Nitrocellulose	9004-70-0	5-20%	F	R11
Isopropyl Alcohol	67-63-0	1-15%	F	R37, R11, R36, R67
Ethyl Alcohol	64-17-5	1-15%	F	R11
n-Butyl Alcohol *	71-36-3	0-6%	XN	R10, R22, R37, R38, R67
Benzyl Alcohol	100-51-6	0-6%	XN	R20, R22

\* Indicates toxic chemical (s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372.

## SECTION 4 – FIRST AID MEASURES

**EYE CONTACT:** Irrigate with copious amounts of water  
Seek medical attention  
**SKIN CONTACT:** wash affected area with soap and water  
**INHALATION:** Remove to fresh air  
Seek medical attention  
**INGESTION:** Do not induce vomiting  
Seek medical attention

## SECTION 5 – FIRE FIGHTING MEASURES

**FLASH POINT:** -4°C or 24°F  
**MAGNITUDE:** Applicable extinguisher type  
**Small Fire:** Carbon Dioxide, Foam or dry chemical extinguishers  
**Large Fire:** Water or foam extinguishers, water fog.  
**PROTECTIVE MEASURES:** Keep away from heat and source of ignition

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS DURING SPILL:** Use suitable protective clothing/equipment.  
Eliminate all source of ignition. No Smoking.  
**ENVIRONMENTAL PRECAUTIONS:** Do not allow to enter water courses or drains  
Dispose in accordance to local regulation.  
Local authorities should be advised if significant spillages cannot be contained.  
**SPILL CLEANUP METHODS:** Contain Spillage with absorbent.  
Mop up small spill  
Sweep up, use absorbent for larger spillages

## SECTION 7 – HANDLING AND STORAGE

**USAGE PRECAUTIONS:** No smoking, Prevent static discharges. Exposure by inhalation or skin contact should be minimized by good industrial hygiene.  
 Vapor is heavier than air, spreads along the ground. Vapor can form an explosive mixture in air prevalent in empty unclean drum/pail.  
 Use non-sparking tools when handling this material

**STORAGE:** Keep containers tightly closed, cool, dry and away from source of ignition, label containers.  
 Eliminate possible point ignition sources, e.g. No Smoking, Open flames, Use proper Bonding and Grounding. Use electrical equipment rated for use with flammables.

---

**SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION**

---

Exposure Levels

Substance	OSHA – PEL - TWA	ACGIH – TLV – TWA
Ethyl Acetate	400 ppm	400 ppm
Butyl Acetate	150 ppm	150 ppm
Nitrocellulose	Not established	Not established
Isopropyl Alcohol	400 ppm	200 ppm
Ethyl Alcohol	1000 ppm	1000 ppm
n-Butyl Alcohol	100 ppm	20 ppm
Benzyl Alcohol	Not established	Not established

Ventilation and extraction of appropriate design is necessary to meet the above levels.

Personal Protection

Appropriate PPE should be worn – Check Local Regulations.

Eye Protection

Clothing / Uniforms

Respirator should be worn if the maximum exposure levels are surpassed

HMIS RATING Hazard Rating: (0=least, 1=slight, 2=moderate, 3=serious, 4=severe)

HEALTH: 2 FIRE: 3 REACTIVITY: 1 PP: G

---

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

---

Appearance: Liquid

Boiling/melting Point: 75 – 80 ° C

Flash Point: - 4° C or 24° F Method: TCC (Tag Closed Cup)

Upper/lower explosion limits: Undefined

Water Solubility: Insoluble

Vapor Density: Heavier than air

Specific Gravity (H2O=1): 0.98-1.05

---

**SECTION 10 – STABILITY AND REACTIVITY**

---

**STABILITY:** Stable under recommended storage conditions. Store away from direct sunlight

**CONDITIONS TO AVOID:** incompatible with strong oxidizing agents. Acids, Alkalizes and Peroxides  
 Flames, Electric spark, static and heat. Do not store at temperatures over 120°

**HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR

---

**SECTION 11 – TOXICOLOGICAL INFORMATION**

---

**INHALATION:** irritation to the respiratory tracts and other various mucosal membranes

**INGESTION:** Harmful if swallowed

**SKIN:** Organic solvents in the product may lead to removal of lipid soluble elements of the skin leading to non-allergic dermatitis upon repeated prolonged contact.

**EYES:** MAY CAUSE IRRITATION, WASH WITH WATER

**HEALTH WARNINGS:** Toxicity –LD 50 Rat- Undefined

---

**SECTION 12 – ECOLOGICAL INFORMATION**

---

**ENVIRONMENTAL HAZARDS:** Product should not be allowed to enter drains or water courses.

Used in large volumes, this product may incur the requirements of the Environmental Protection Act (pollution control/air) Environmental Protection Agency.

---

**SECTION 13 – DISPOSAL CONSIDERATIONS**

---

**DISPOSAL METHODS:** Dispose of product accordance with local, county, state and federal government regulations.

---

**SECTION 14 – TRANSPORT INFORMATION**

---

Proper Shipping Name : Paint  
Technical Name : Nitrocellulose Lacquer (Ethyl Acetate, Butyl Acetate)  
U.N. number : 1263  
DOT Hazard Class : 3 (Flammable Liquid)  
Packing Group : II  
Flash Point : - 4°C or 24° F TCC (Tag Closed Cup)  
ADR : Class 3; F1

---

**SECTION 15 – REGULATORY INFORMATION**

---

**UNITED STATES FEDERAL REGULATIONS:**

SARA: See section 2 for reportable material

SARA TITLE III: See Section 2

CERCLA: See Section 2

TSCA: - Components in this product have been verified as being on the TSCA Inventory and have been classified in accordance with the hazard criteria of the CFR and all information required.-

**STATE REGULATIONS:**

Proposition 65: None

EU Risk Phrases : R10 Flammable  
R11 Highly Flammable  
R20 Harmful by inhalation  
R21 Harmful in contact with skin  
R22 Harmful if swallowed  
R36 Irritating to eyes  
R37 Irritating to respiratory system  
R38 Irritating to skin  
R41 Risk of serious damage to eyes  
R43 May cause sensitization by skin contact  
R65 Harmful: may cause lung damage if swallowed  
R66 Repeated exposure may cause skin dryness or cracking  
R67 Vapors may cause drowsiness and dizziness.

EU Safety Phrases : S16 Keep away from sources of ignition- **No Smoking**  
S23 Do not breathe vapor.  
S25 Avoid contact with eyes.  
S29 Do not empty into drains.  
S33 Take precautionary measures against.

Hazard Symbols : Xn - Harmful  
Xi - Irritant  
F - Highly Flammable

NOTE: The appropriate Risk Phrases and Hazard Symbols pertaining to this product are listed Section 2.

---

**SECTION 16 – OTHER INFORMATION**

---

**REVISION DATE:** 3 January 2021

**NOTE:** The data and recommendations herein are based on information available to us. No express or implied warranty is given. Product is distributed without any warranty express or implied. User assumes all risks and responsibility for distributing and marketing of this product.